

Amendments to the Claims

This listing of claims replaces all prior versions and listings of claims in the application:

- Sub B1
1. (Currently Canceled) Please cancel claim 1 without prejudice or disclaimer.
  2. (Currently Amended) The valve of claim 1 wherein the throttling cage is offset in the cavity away from the second fluid passage.
  3. (Currently Amended) The valve of claim 1 wherein an annular volume between the throttling cage and a wall of the cavity is smallest in an area of the cavity opposite the second fluid passage.
  4. (Currently Amended) The valve of claim 1 wherein at least one of the flow ports facing the second fluid passage is larger than at least one of the other flow ports.
  5. (Currently Amended) The valve of claim 1 wherein a flow port facing the second fluid passage is larger than any of the other flow ports.
  6. (Currently Amended) The valve of claim 1 A valve comprising:  
a valve body defining an interior cavity in communication with a first fluid passage and a  
second fluid passage, the volume of the cavity is substantially equally distributed about a central  
axis;  
a tubular throttling cage in the cavity and in communication with the first fluid passage,  
the tubular throttling cage having a plurality of flow ports arranged about a perimeter of the  
throttling cage, wherein fluid flows between the first fluid passage and the second fluid passage  
through the throttling cage, a longitudinal axis of the throttling cage is positioned offset from the  
central axis of the cavity, and wherein the flow ports are angled towards the second fluid  
passage; and

Sub  
B1 a plug closely received in the throttling cage and moveable about the longitudinal axis to selectively cover the flow ports thereby restricting flow between the first fluid passage and the second fluid passage.

7. (Original) The valve of claim 6 wherein the flow ports pass substantially straight through the throttling cage.

A-  
sent 8. (Currently Amended) The valve of claim ~~1~~ 6 wherein the throttling cage has a triangular flow splitter.

9. (Original) The valve of claim 8 wherein the triangular flow splitter is in the portion of the throttling cage opposite the second fluid passage.

10. (Currently Amended) The valve of claim ~~1~~ 6 wherein the throttling cage is substantially sealed to the valve body.

July 31  
11. (Currently Canceled) Please cancel claim 11 without prejudice or disclaimer.

12. (Currently Amended) The fluid flow control device of claim ~~11~~ 14 wherein at least one of the lateral ports is larger than the other lateral ports.

13. (Currently Amended) The fluid flow control device of claim ~~11~~ 14 wherein a lateral port facing the second fluid passage is larger than at least one of the other lateral ports.

14. (Currently Amended) ~~The fluid flow control device of claim 11~~ A fluid flow control device, comprising:

a flow body having an internal chamber;

a first fluid passage intersecting the chamber;

a second fluid passage intersecting the chamber;

a tubular member residing in the internal chamber, the tubular member being in communication with the first fluid passage and having a plurality of lateral ports, wherein the lateral ports are angled towards the second fluid passage; and  
a plug adapted for movement in an interior of the tubular member to selectively cover a portion of the ports;  
wherein an annular volume between the tubular member and the flow body is smallest opposite the second fluid passage.

15. (Original) The fluid flow control device of claim 14 wherein the lateral ports pass substantially straight through the tubular member.

16. (Currently Amended) The fluid flow control device of claim ~~11~~ 14 wherein two adjacent lateral ports form a triangular flow splitter in the tubular member.

17. (Original) The fluid flow control device of claim 16 wherein a lateral port opposite the triangular flow splitter is larger than at least one of the other lateral ports.

Sub B1 18. (Original) A throttling cage for a globe valve, comprising:  
a tubular body having a plurality of laterally oriented flow ports, the flow ports being substantially straight passages through the tubular body, wherein one of the ports directs flow in a first direction, and at least one other port is angled to direct flow towards the first direction.

A1 19. (Original) The throttling cage of claim 18 wherein one of the flow ports is larger than the other flow ports.

20. (Original) The throttling cage of claim 18 wherein at least one of the flow ports is larger than at least one of the other flow ports.

21. (Original) The throttling cage of claim 18 wherein two adjacent flow ports form a triangular flow splitter.

July 13<sup>1</sup> 22. (Currently Amended) A valve comprising:  
a valve body defining an interior cavity in communication with a first fluid passage and a second fluid passage;

a tubular throttling cage in the cavity having an open end in communication with the first fluid passage and a plurality of flow ports arranged about a perimeter of the throttling cage, the flow ports being substantially straight passages through the throttling cage, wherein one of the flow ports directs flow in a first direction and at least one of the other ports is angled to direct flow towards the first direction, and wherein fluid flows between the first fluid passage and the second fluid passage through the throttling cage; and

A1  
a plug closely received in the throttling cage and moveable in the throttling cage to selectively cover the flow ports thereby restricting flow between the first fluid passage and the second fluid passage.

23. (Original) The valve of claim 22 wherein at least one of the flow ports is larger than at least one of the other flow ports.

24. (Original) The valve of claim 22 wherein an annular volume between the throttling cage and a wall of the cavity is smallest in an area of the cavity opposite the second fluid passage.

Sub B1 25. (Currently Canceled) Please cancel claim 25 without prejudice or disclaimer.

26. (Currently Amended) The valve of claim ~~25~~ 27 wherein a lateral flow port facing the outlet is larger than at least one of the other lateral flow ports.

A1 sub 27. (Currently Amended) ~~The valve of claim 25~~ A valve, comprising:  
a flow body having an internal chamber;  
an inlet intersecting the chamber;  
an outlet intersecting the chamber;  
a tubular member residing in the internal chamber, the tubular member in communication  
with the inlet and having a plurality of lateral ports in communication with the chamber, wherein  
at least two of the lateral ports are angled towards the outlet; and  
a plug movable in an interior of the tubular member to selectively cover a portion of the  
ports;  
wherein an annular volume between the tubular member and the flow body is smallest  
opposite the outlet.

28. (Currently Amended) The valve of claim ~~25~~ 27 further comprising a triangular flow splitter in the tubular member opposite the outlet.